

APPLICATION OF GENERAL CONDITIONS:

All of the work described herein is subject ~~to~~ to the foregoing General Conditions, these General Conditions becoming a part of this specification, and all work shall be carried on in accordance therewith.

WORK INCLUDED:

This contract shall include the furnishing and setting of all glass throughout the building as shown or specified, except wire glass in skylights.

Any glass not particularly shown or mentioned, but which is clearly necessary for the completion of the building, shall be furnished, and all glass shall be installed in the best possible manner.

PUTTYING:

All lights, unless otherwise specified, shall be well bedded, back-puttied, with best bolted whitening and raw linseed oil putty. All glass shall be secured in place with glazing fillets.

STOPS:

All glass shall be bedded and back-puttied and secured in place with stops, wood or metal.

GRADING RULES:

All glass and glazing shall conform to the various grades as covered by the National Glass Distributors' Association's pamphlet entitled "Glass and Glazing".

PLATE GLASS:

Glaze all doors interior and exterior, (where shown to be glazed) all exterior sash, sash of arcade and display case sash with "Standard polished plate glass" 3/16" thick. Sash of arcade on display case shall be set in lead cames as detailed.

PLATE GLASS MIRRORS:

Furnish and install one 18"x 24" best quality 1/4" polished plate glass mirror in each toilet room and dressing room.

Mirrors shall have felt backing and shall be set in wood frames furnished by the carpenter contractor. Set mirrors at least 1/8" free of wall, and at place and height directed by the Architect.

OBSCURE GLASS:

Where glass are shown "obscure" on the drawings same shall be best quality Carnation figured glass, or other approved glass.

DOUBLE STRENGTH:

Glass for all transoms, for cases doors etc., not otherwise shown or specified shall be "AA" quality double strength window glass. All this glass shall be delivered to the building in the original boxes with the manufacturer's name on same.

PROTECTION AND DAMAGE:

The glazing contractor shall protect all glass and putty from damage where necessary, and he will be held responsible for all broken glass and must replace same and leave the whole in perfect order when the building is turned over to the owner.

CLEANING:

At completion, or when so ordered, this contractor shall clean all glass of all putty, oil, paint, varnish, plaster, or other defacement; wash and leave perfectly clean and clear, ready for occupancy, and satisfactory to the architect.