

70.

SOUND PROOFING

APPLICATION OF GENERAL CONDITIONS:

All of the work described herein is subject to the foregoing General Conditions, these General Conditions becoming a part of this specification, and all work shall be carried on in accordance therewith.

WORK INCLUDED:

The ceilings of Cafeteria #27, Ball rm. #18, Concourse #19 & Entry #28, shall be sound proofed with the Johns-Manville Nashkote A System of Acoustical Treatment, furnished and installed by the manufacturer strictly in accordance with the following specification.

Directly to the plaster scratch coat apply by the plastering contractor, shall be attached Johns-Manville Asbestos Akoustikos Felt, $\frac{1}{2}$ " thick, by means of moisture and heat-resisting cement.

Felt surface shall be treated with special sizing and while sizing is wet a layer of batiste muslin shall be applied into the size over the surface of the Felt so that no bubbles or air pockets are left so that muslin adheres to the Felt surface, smoothly and securely.

When sizing is thoroughly dry surface shall be finished with Johns-Manville special acoustical paint, the color to be selected by architect, and applied in such a manner that no seams or lumps shall be shown and that the surface shall be entirely free from batten stripping or moulding.

All work shall be installed when so directed by the Architect and all painting of ceilings shall be done by the best skilled painters and all work shall be to the entire satisfaction of the Architect.